



VPF NR



VPF NR series pocketfilters are designed for low pressure drop needed applications. With high efficiency of ePM1 80% it reaches up to B energy class efficiency.

- High to medium energy efficiency with B,C and D energy classes
- Very good dust holding capacity
- Environmentally friendly pocketfilter product
- Low life cycle carbon footprint
- Suitable for Nordic weather (snow and high humidity) conditions

Applications

Filter media

Filter frame

Filtering efficiency

Waste disposal

Operating temperature

Humidity resistance

High efficiency and low pressure drop HVAC and industrial applications

Synthetic NanoWave multilayer material

Solid multipiece wood and plastic compound or plastic frame

ePM1 80% and ePM10 65% by ISO 16890 ; M5, F8-9 by EN779

Waste-to-Energy 100% incinerable

Max 70 °C

100 % relative humidity resistance

Product name	Filter class	Energy kWh/a	Energy class	Width	Hight	Lenght	Bags	Airflow m³/s
VPF NR ePM1 80% 592 592 650 10	ISO ePM1 80%	1347	B	592	592	650	10	0,944
VPF NR ePM1 80% 892 287 650 15	ISO ePM1 80%		B	892	287	650	15	0,690
VPF NR ePM1 80% 592 892 650 10	ISO ePM1 80%		B	592	892	650	10	1,422
VPF NR ePM1 80% 592 490 650 10	ISO ePM1 80%		B	592	490	650	10	0,781
VPF NR ePM1 80% 592 287 650 10	ISO ePM1 80%		B	592	287	650	10	0,458
VPF NR ePM1 80% 490 592 650 8	ISO ePM1 80%		B	490	592	650	8	0,781
VPF NR ePM1 80% 490 490 650 8	ISO ePM1 80%		B	490	490	650	8	0,647
VPF NR ePM1 80% 287 892 650 5	ISO ePM1 80%		B	287	892	650	5	0,690
VPF NR ePM1 80% 287 592 650 5	ISO ePM1 80%		B	287	592	650	5	0,458
VPF NR ePM1 80% 287 490 650 5	ISO ePM1 80%			287	490	650	5	0,379
VPF NR ePM1 80% 287 287 650 5	ISO ePM1 80%		B	287	287	650	5	0,222
Product name	Filter class	Energy kWh/a	Energy class	Width	Hight	Lenght	Bags	Airflow m³/s
VPF NR ePM1 80% 592 592 525 10	ISO ePM1 80%	1646	C	592	592	525	10	0,944
VPF NR ePM1 80% 892 287 525 15	ISO ePM1 80%		C	892	287	525	15	0,690
VPF NR ePM1 80% 592 892 525 10	ISO ePM1 80%		C	592	892	525	10	1,422
VPF NR ePM1 80% 592 490 525 10	ISO ePM1 80%		C	592	490	525	10	0,781
VPF NR ePM1 80% 592 287 525 10	ISO ePM1 80%		C	592	287	525	10	0,458
VPF NR ePM1 80% 490 592 525 8	ISO ePM1 80%		C	490	592	525	8	0,781
VPF NR ePM1 80% 490 490 525 8	ISO ePM1 80%		C	490	490	525	8	0,647
VPF NR ePM1 80% 287 892 525 5	ISO ePM1 80%		C	287	892	525	5	0,690
VPF NR ePM1 80% 287 592 525 5	ISO ePM1 80%		C	287	592	525	5	0,458
VPF NR ePM1 80% 287 490 525 5	ISO ePM1 80%			287	490	525	5	0,379
VPF NR ePM1 80% 287 287 525 5	ISO ePM1 80%		C	287	287	525	5	0,222
Product name	Filter class	Energy kWh/a	Energy class	Width	Hight	Lenght	Bags	Airflow m³/s
VPF NR ePM1 80% 592 592 650 8	ISO ePM1 80%	1388	B	592	592	650	8	0,944
VPF NR ePM1 80% 892 287 650 12	ISO ePM1 80%		B	892	287	650	12	0,690
VPF NR ePM1 80% 592 892 650 8	ISO ePM1 80%		B	592	892	650	8	1,422
VPF NR ePM1 80% 592 490 650 8	ISO ePM1 80%		B	592	490	650	8	0,781
VPF NR ePM1 80% 592 287 650 8	ISO ePM1 80%		B	592	287	650	8	0,458
VPF NR ePM1 80% 490 592 650 7	ISO ePM1 80%			490	592	650	7	0,781
VPF NR ePM1 80% 490 490 650 7	ISO ePM1 80%			490	490	650	7	0,647
VPF NR ePM1 80% 287 892 650 4	ISO ePM1 80%		B	287	892	650	4	0,690
VPF NR ePM1 80% 287 592 650 4	ISO ePM1 80%		B	287	592	650	4	0,458
VPF NR ePM1 80% 287 490 650 4	ISO ePM1 80%			287	490	650	4	0,379
VPF NR ePM1 80% 287 287 650 4	ISO ePM1 80%		B	287	287	650	4	0,222

VADO FILTERS

VPF N Pocketfilters

Product name	Filter class	Energy kWh/a	Energy class	Width	Hight	Lenght	Bags	Airflow m ³ /s
VPF NR ePM1 80% 592 592 525 8	ISO ePM1 80%	1983	D	592	592	525	8	0,944
VPF NR ePM1 80% 892 287 525 12	ISO ePM1 80%		D	892	287	525	12	0,690
VPF NR ePM1 80% 592 892 525 8	ISO ePM1 80%		D	592	892	525	8	1,422
VPF NR ePM1 80% 592 490 525 8	ISO ePM1 80%		D	592	490	525	8	0,781
VPF NR ePM1 80% 592 287 525 8	ISO ePM1 80%		D	592	287	525	8	0,458
VPF NR ePM1 80% 490 592 525 7	ISO ePM1 80%			490	592	525	7	0,781
VPF NR ePM1 80% 490 490 525 7	ISO ePM1 80%			490	490	525	7	0,647
VPF NR ePM1 80% 287 892 525 4	ISO ePM1 80%		D	287	892	525	4	0,690
VPF NR ePM1 80% 287 592 525 4	ISO ePM1 80%		D	287	592	525	4	0,458
VPF NR ePM1 80% 287 490 525 4	ISO ePM1 80%			287	490	525	4	0,379
VPF NR ePM1 80% 287 287 525 4	ISO ePM1 80%		D	287	287	525	4	0,222

Product name	Filter class	Energy kWh/a	Energy class	Width	Hight	Lenght	Bags	Airflow m ³ /s
VPF NR ePM10 60% 592 592 550 8	ISO ePM10 65%	696	B	592	592	550	8	0,944
VPF NR ePM10 60% 892 287 525 12	ISO ePM10 65%		B	892	287	550	12	0,690
VPF NR ePM10 60% 592 892 525 8	ISO ePM10 65%		B	592	892	550	8	1,422
VPF NR ePM10 60% 592 490 525 8	ISO ePM10 65%		B	592	490	550	8	0,781
VPF NR ePM10 60% 592 287 525 8	ISO ePM10 65%		B	592	287	550	8	0,458
VPF NR ePM10 60% 490 592 525 7	ISO ePM10 65%			490	592	550	7	0,781
VPF NR ePM10 60% 490 490 525 7	ISO ePM10 65%			490	490	550	7	0,647
VPF NR ePM10 60% 287 892 525 4	ISO ePM10 65%		B	287	892	550	4	0,690
VPF NR ePM10 60% 287 592 525 4	ISO ePM10 65%		B	287	592	550	4	0,458
VPF NR ePM10 60% 287 490 525 4	ISO ePM10 65%			287	490	550	4	0,379
VPF NR ePM10 60% 287 287 525 4	ISO ePM10 65%		B	287	287	550	4	0,222